

- Quick Internet Setup
- General
- Network Map
- Guest Network
- AiProtection
- Adaptive QoS
- Traffic Analyzer
- Game
- Open NAT
- USB Application
- AiCloud 2.0

- Advanced Settings
- Wireless
- LAN
- WAN

Operation Mode: Wireless router Firmware Version: 3.0.0.4.384\_81858 SSID: ASUS2.4 ASUS5.0

- General
- WPS
- WDS
- Wireless MAC Filter
- RADIUS Setting
- Professional
- Roaming Block List

### Wireless - General

Set up the wireless related information below.

Enable Smart Connect	<input checked="" type="checkbox"/> ON <a href="#">Smart Connect Rule</a>
Smart Connect	Dual-Band Smart Connect (2.4GHz and 5GHz)
Network Name (SSID)	ASUS2.4
Hide SSID	<input type="radio"/> Yes <input checked="" type="radio"/> No
Wireless Mode	Auto
Authentication Method	WPA2-Personal
WPA Encryption	AES
WPA Pre-Shared Key	1Fishing1
Protected Management Frames	Capable
Group Key Rotation Interval	3600

2.4 GHz	
Channel bandwidth	20/40 MHz
Screenshot	Auto <span>Current Control Channel: 8</span> <input type="checkbox"/> Auto select channel including channel 12, 13